

BELZONA SLOPES CATALYST

ID: 10089



PROBLEM

Concrete was deteriorating because lack of protection from the chemicals over time.

APPLICATION SITUATION

Belzona was able to only have the area down for four days. Other products was going to take several more days to apply costing the company 10,000's of dollars more of down time.

APPLICATION METHOD

Grit blasted area with aluminum oxide, troweled on Belzona 4124 to make floor to wall transitions. Applied two coats of Belzona 5811 using brushes.

BELZONA FACTS

By using Belzona for this application the client save three down day's saving them ten's of thousands of dollars not to mention the employees can wash down a lot faster and easier.

INDUSTRY

Chemical & Petrochemical

LOCATION

Lafayette LA

APPLICATION DATE

November 2025

PRODUCTS

Belzona 4124 (Bulkfill)
Belzona 4154 (Bulkfill Resin)
Belzona 5811 (Immersion Grade)

SUBSTRATE

Concrete

PHOTOS

1. Contractors setting up the pump bases.
2. Containment after being cleaned and grit blasted.
3. Containment during first coat of Belzona 5811.
4. Containment after top coat of Belzona 5811.

For more examples of Belzona Know-How in Action, please visit khia.belzona.com

Belzona products are manufactured
under an ISO 9001 Registered
Quality Management System.

www.belzona.com

