

BELZONA PREVENTS COSTLY LEAKAGE

ID: 1024



PROBLEM

The ingress of limestone particles into the 10-20mm gap between the tubular screw conveyor and its housing leads to wear and leakage of milling media outside the mill.

APPLICATION SITUATION

Ball Mill used to grind limestone for cement production.

APPLICATION METHOD

Application was carried out in accordance with modified versions of Belzona Know How Leaflet GSS-9 and VPF-2.

BELZONA FACTS

The Belzona was chosen in order to prolong the life of tubular screw conveyor. The customer had used different epoxy-based products to solve the problem but with limited success. Welding was not considered due to high cost and stress buildup. The Belzona solution proved to be much easier and faster to apply saving the plant more than 5000 euros in replacement and maintenance costs.

INDUSTRY

General Industry

LOCATION

Cement plant, Bulgaria

APPLICATION DATE

March, 2008

PRODUCTS

Belzona 1812 (Ceramic Carbide FP)

SUBSTRATE

Carbon Steel

PHOTOS

1. View of the gap between the tabular screw conveyor and the housing
2. Belzona 1812 being applied
3. Completed application

For more examples of Belzona Know-How in Action, please visit khia.belzona.com

Belzona products are manufactured under an ISO 9001 Registered Quality Management System.

www.belzona.com

