

BELZONA MAINTAINS POWER PLANT MAIN COOLING WATER SYSTEM

ID: 4385



PROBLEM

The continuous flow of water through the system had caused the concrete construction to wear both upstream and downstream of the pump, as well as inside the pump volute. This erosive wear had led to micro cracking of the concrete. In addition the rough concrete surface had led to a loss of efficiency as the worn concrete walls created a more turbulent flow.

APPLICATION SITUATION

Large water pumps with concrete volutes circulating the cooling water for the Power Station

APPLICATION METHOD

The application was carried out in accordance with Belzona Know-How System Leaflet CEP-10. The upper 15 linear metres were protected using Belzona® 5811. The severely eroded section where pipe turned 90° was restored using Belzona® 4111 across an area of approximately 20m². The area was then over-coated with Belzona® 1341 to create smooth surface with optimum efficiency. Another 20m² section, right underneath the pump, was also repaired and protected in the same way. Finally, the pump outlet was also restored over an area of 130m² using the same system.

BELZONA FACTS

This restoration procedure was repeated for all of the cooling system lines at this power station. The application was completed by a team of 17 individuals with a time frame of two and a half weeks per system. The entire application required several tonnes of Belzona materials.

INDUSTRY

Power

LOCATION

Nuclear Power plant, France

APPLICATION DATE

July 2012

PRODUCTS

Belzona 5811 (Immersion Grade)
Belzona 4111 (Magma-Quartz)
Belzona 1341 (Supermetalgilde)

SUBSTRATE

Concrete

PHOTOS

1. Volute prior to application
2. Application of Belzona 4111 completed
3. Application of Belzona 1341
4. View of the volute following repair

For more examples of Belzona Know-How in Action, please visit khia.belzona.com

Belzona products are manufactured
under an ISO 9001 Registered
Quality Management System.

www.belzona.com

