

BELZONA PROTECTS HYDROELECTRIC DAM COMPONENT

ID: 4656



PROBLEM

High volume of river water will flow over the steel component and client wanted a coating suitable for permanent immersion and to protect from corrosion.

APPLICATION SITUATION

The fabricated pieces will be one of the first components to construct the dam used to generate hydroelectric power. The coated steel will be cast into concrete with hundreds of thousands of gallons of water will flow over the completed application.

APPLICATION METHOD

Application was carried out by brush in accordance with Belzona Know-How System Leaflet CEP-4

BELZONA FACTS

The project was carried out according to the specification from United States Corps of Engineers.

INDUSTRY

Power

LOCATION

Brampton, Ontario, Canada

APPLICATION DATE

April 2013

PRODUCTS

Belzona 5811 (Immersion Grade)

SUBSTRATE

Carbon steel

PHOTOS

1. Abrasive blasted substrate awaiting coating
2. Application of 1st coat of Belzona 5811 (Grey)
3. Completed application of 1st coat of Belzona 5811 (Grey)
4. Completed application of 2nd coat of Belzona 5811 (Black)

For more examples of Belzona Know-How in Action, please visit khia.belzona.com

Belzona products are manufactured under an ISO 9001 Registered Quality Management System.

www.belzona.com

