

BELZONA REPAIRS CRUSHER'S ADJUSTMENT RING

ID: 5087



PROBLEM

The worn-out strip prevented the crusher from functioning well.

APPLICATION SITUATION

Repair of the ring strip during an emergency stop.

APPLICATION METHOD

First, the surface was prepared with emery cloth. Afterwards, Belzona 9411 was applied to the surface of the crusher in order to later apply Belzona 1111 to the worn-out ring and join the pieces together to mold Belzona 1111 between the two pieces.

BELZONA FACTS

The mine did not have another ring to replace the damaged one and was not able to stop the operations. The application of Belzona 1111 and Belzona 9411 solved the problem and enabled the crusher to continue working until the new ring arrived.

INDUSTRY

Mining & Quarrying

LOCATION

Mine, Chile

APPLICATION DATE

February 2006

PRODUCTS

Belzona 1111 (Super Metal)
Belzona 9411 (Release Agent)

SUBSTRATE

Steel

PHOTOS

1. Damage on the ring of the crusher
2. Application of Belzona 9411 on the surface of the crusher
3. Application of Belzona 1111 on the strip of the worn-out ring
4. The ring repaired with Belzona 1111

For more examples of Belzona Know-How in Action, please visit khia.belzona.com

Belzona products are manufactured
under an ISO 9001 Registered
Quality Management System.

www.belzona.com

