

BOW THRUSTER TUNNEL PROTECTED

ID: 5600



PROBLEM

Thruster tunnel was pitted and eroded in areas near thruster propulsion unit. Bi-metallic corrosion was also a component of the deterioration.

APPLICATION SITUATION

Vessel in shipyard required resurfacing of bow thruster tunnel before launch. The owner was unaware of the problem prior to the vessel being hauled. Timely response was in order.

APPLICATION METHOD

Tunnel was prepared by first removing several layers of bottom paint and then abrasive blasting to achieve a 3 mil profile. Belzona 1311 was applied to fill the pitting and erosion prior to the application of 2 coats of Belzona 1321.

BELZONA FACTS

Vessel owner sought options to cutting out and replacing pitted bow thruster tunnel in private steel yacht. Prior experience in use of Belzona with his dredging company had convinced him Belzona materials were the right option.

INDUSTRY

Marine

LOCATION

Pacific Northwest

APPLICATION DATE

April 2015

PRODUCTS

Belzona 1311 (Ceramic R-Metal)
Belzona 1321 (Ceramic S-Metal)

SUBSTRATE

Carbon steel

PHOTOS

1. Vessel out of water with hatch built around thruster tunnel for containment.
2. Tunnel prepared with abrasive blast. Note significant pitting on upper surfaces.
3. Belzona 1311 applied to pitted areas as seen from inside vessel.
4. Two coat application of Belzona 1321. Bottom paint will be lapped over Belzona 1321 at tunnel edge.

For more examples of Belzona Know-How in Action, please visit khia.belzona.com

Belzona products are manufactured under an ISO 9001 Registered Quality Management System.

www.belzona.com

