

RECESSED BELZONA SELF LEVELLING LINE MARKING

ID: 6098



PROBLEM

Line markings in the facilities of this leading waste handling company typically only lasted days before being destroyed by the heavy plant shovels. A previous Belzona trial had proved very successful and so was again chosen as the solution for this site entrance.

APPLICATION SITUATION

Line Marking in Heavy Plant Areas

APPLICATION METHOD

Application was carried out in accordance with Belzona Know-How System Leaflet FPA-4. A channel was cut into the floor about 160mm wide and 5mm deep. A self-levelling screed was mixed using 3:1 Belzona 5231 and Belzona 9221, before being poured into the channel.

BELZONA FACTS

This self-levelling mix of Belzona 5231 offered a cost effective and solvent free application that would not shrink. The recessed application has survived constant heavy traffic with shovels scraping over it as the waste is moved into the facility.

INDUSTRY

General Industry

LOCATION

Waste Recycling Plant, UK

APPLICATION DATE

2012

PRODUCTS

Belzona 5231 (SG Laminate)

Belzona 9221 (Surefoot Aggregate White)

SUBSTRATE

Concrete

PHOTOS

1. Entrance with lines recessed 5mm
2. Channels conditioned with Belzona 4911
3. Line marking with Belzona 5231

For more examples of Belzona Know-How in Action, please visit khia.belzona.com

Belzona products are manufactured
under an ISO 9001 Registered
Quality Management System.

www.belzona.com

