

BELZONA REPAIR AND COATING INTERNAL SURFACE OF ROTOR CAN OF PREHEAT UNIT AND REPAIR SHAFT OF COOKER UNIT

ID: 7709



PROBLEM

The damage area cause by erosion and corrosion

APPLICATION SITUATION

Repair and coating internal surface of rotor can of preheat unit and repair shaft of cooker unit.

APPLICATION METHOD

Working details for rotor can:

1. Carbon steel surface will be prepare by copper slug to give a minimum depth at 75 microns and surface cleanliness by Sa 2.5
2. Clean and brush away any loose contaminate, cleaning with vacuum cleaner machine then cleaning the surface with MEK.
3. Apply two coats system of Belzona 1391S Ceramic HT at dry film thickness 500 microns.

Working details for shaft:

1. Surface preparation with hand grinding machine.
2. Repair corrode area with Belzona 1111 Supermetal.

BELZONA FACTS

Belzona 1391S can operate at high temperature under immersed conditions , rapid spray application results in reduced downtime , excellent chemical resistance against a wide range of chemicals , excellent corrosion protection

INDUSTRY

Food & Drink

LOCATION

Bangkok, Thailand

APPLICATION DATE

27 February 2017

PRODUCTS

Belzona 1391S
Belzona 1111 (Super Metal)

SUBSTRATE

Carbon Steel

PHOTOS

1. The rotor damage area cause by erosion and corrosion
2. Damage shaft surface at cooker unit
3. Application complete with Belzona 1391S for rotor
4. Application complete with Belzona 1111 for shaft

For more examples of Belzona Know-How in Action, please visit khia.belzona.com

Belzona products are manufactured
under an ISO 9001 Registered
Quality Management System.

www.belzona.com

