

HIGH SPEED FERRY PROPELLER CAVITATION DAMAGE REPAIR

ID: 8145



PROBLEM

Cavitation damage on ferry propellers causing lower hydrodynamic efficiency and less propulsion capabilities.

APPLICATION SITUATION

Cavitation damage on both propellers of high speed ferry. The damage is more intense on the blade leading edges. The damaged propellers causing ferry two operate with some vibration and less hydrodynamic efficiency.

APPLICATION METHOD

Application was carried out in accordance with Belzona Know-How System Leaflet SOS-01. Propeller surface blasted in blasting cabin. Surface was cleaned with Belzona 9111 (Cleaner & Degreaser) after blasting. Immediately following surface preparation Belzona 1311 (Ceramic R-Metal) is applied on the surface. After the product is cured, the surface was grinded and faired to achieve smooth surface.

BELZONA FACTS

Propeller replacement would be very costly too time consuming. Low cost and parmanent solution with Belzona.

INDUSTRY

Marine

LOCATION

Tuzla, ISTANBUL, TURKEY

APPLICATION DATE

April 2019

PRODUCTS

Belzona 1311 (Ceramic R-Metal)

Belzona 9111 (Cleaner & Degreaser)

SUBSTRATE

Bronze

PHOTOS

1. Cavitation damage on the propeller.
2. After surface preparation.
3. Application Belzona 1311 (Ceramic R-Metal).
4. The surface faired after Belzona application.

For more examples of Belzona Know-How in Action, please visit khia.belzona.com

Belzona products are manufactured
under an ISO 9001 Registered
Quality Management System.

www.belzona.com

