

CHEMICAL RESISTANT BELZONA LINING APPLIED TO INTERIOR OF MIXER DRUM

ID: 8167



PROBLEM

Following the success of Belzona systems in the past, the client requested that Belzona apply a chemical resistant coating system to a newly fabricated mixer drum to extend the life expectancy.

APPLICATION SITUATION

Newly fabricated mixer drum (2.2m length x 1.5m diameter) used in a chemically aggressive process.

APPLICATION METHOD

The internals of the drum were prepared using conventional grit blasting methods to the required standard. The paste grade Belzona 1111 was used to fill the voids between the blades. Once cured, three coats of Belzona 4341 were applied by brush. The lining was allowed to cure for 12 hours. Following that 80°C heat was applied for 4 hours to force cure the product and maximise chemical resistance properties. The product was applied in accordance with Belzona System Leaflet TCC-5.

BELZONA FACTS

Belzona have carried out several protective coating applications for the client in the past so they were confident that Belzona could provide the required chemical resistance to the mixer drum. The application was undertaken at Belzona's fully equipped workshop, allowing them to provide a full turn key service.

INDUSTRY

General Industry

LOCATION

Chemical Manufacturer, Bristol, UK

APPLICATION DATE

December 2018

PRODUCTS

Belzona 1111 (Super Metal)
Belzona 4341 (Magma CR4)

SUBSTRATE

Steel

PHOTOS

1. Mixer drum delivered to workshop
2. Internal substrate prepared
3. Voids between blades filled
4. Completed lining

For more examples of Belzona Know-How in Action, please visit khia.belzona.com

Belzona products are manufactured
under an ISO 9001 Registered
Quality Management System.

www.belzona.com

