

BELZONA PROVIDES LEADING EDGE PROTECTION (LEP)

ID: 8583



PROBLEM

A cooling tower with 4 x 9mØ cells, each with 9 x 4.5m blades was to be refurbished, the main part of the works was to replace the blades. This was mainly due to wear and expected erosion leading to failure of the blades. Our client stepped in to offer a solution to keep the existing blades and coat them to protect the client's assets.

APPLICATION SITUATION

36 x 4.5m x 750mm blades were to be protected using Belzona's recently released protection coating, specifically designed for Leading Edge Protection.

APPLICATION METHOD

Training was given from the UK Sales Technical team to the contractors at their works. The blades were sanded to provide a key, then 2 x coats of 5811 were applied to the total surfaces of the fan blades. After curing, the 5811 was again abraded along on the leading edge, approx 80mm either side of the blade's leading edge to the length of the blade. 2 coats of 5721 was then applied to complete the protective application.

BELZONA FACTS

The cost to replace the blades could have been between 5 and 25 times that of the cost of the Belzona materials used. This application has also paved the way for the Contractor to offer the same service on many other sites.

INDUSTRY

Power

LOCATION

Doncaster

APPLICATION DATE

September 2021

PRODUCTS

Belzona 5811 (immersion grade)
Belzona 5721

SUBSTRATE

Composite fibre

PHOTOS

1. Training taking place
2. Blades awaiting preparation
3. Finished blades awaiting dispatch to site
4. Closer detail of finished LEP and full body protection coating

For more examples of Belzona Know-How in Action, please visit khia.belzona.com

Belzona products are manufactured under an ISO 9001 Registered Quality Management System.

www.belzona.com

