

RUBBER LINING ON LIMESTONE FILTER TANK REPLACED WITH BELZONA'S EPOXY LINING

ID: 9006



PROBLEM

Cracks, blisters, delaminations and alligatoring were found in the existing rubber lining of the tank after a long period of use without maintenance.

APPLICATION SITUATION

A patch repair option of the rubber lining was replaced by the use of Belzona rebuilding paste grade and protective coating.

APPLICATION METHOD

Damaged areas of the existing rubber lining were removed and the exposed metal surface was grit blasted. Exposed deeply pitted areas were filled with Belzona 1111 and rebuilt up to 1 mm to compensate for metal loss. Multiple coats of Belzona 1321 were applied by brush for extra protection.

BELZONA FACTS

The Belzona solution is easy to install and has been proven in service to last longer than conventional rubber linings applied to tank inner surfaces. It is also cost-effective, requiring less equipment to apply and the usual manpower required to restore the wall thickness and apply the protective coating.

INDUSTRY

Power

LOCATION

Ras Laffan, Doha, Qatar

APPLICATION DATE

June 2016

PRODUCTS

Belzona 1111 (Super Metal)
Belzona 1321 (Ceramic S-Metal)

SUBSTRATE

Carbon steel

PHOTOS

1. Cracking on the original rubber lining
2. Delaminations on the original rubber lining
3. Initial coat of Belzona 1321 being applied
4. Application completed and protected tank inner surfaces

For more examples of Belzona Know-How in Action, please visit khia.belzona.com

Belzona products are manufactured under an ISO 9001 Registered Quality Management System.

www.belzona.com

