

BELZONA 2111 COVERS THE CLIPS

ID: 9491



PROBLEM

The clip joints on this belt were constantly wearing down prematurely and causing the belt to come apart.

APPLICATION SITUATION

The clip joint on this belt was needing to be replaced every couple months to keep the belt operational. This belt moved lumber scraps in a lumber mill to the chipper and could have a wide variety of sizes of scrap wood on it. When this belt would fail, it would make a large mess of scrap wood and back up the production line until it was repaired. Applying Belzona 2111 over the clip joint protected the clips from wear and prevented the constant unscheduled shutdowns.

APPLICATION METHOD

Washed the belt and clip joint with soapy water and allowed it to dry. The surface of the rubber was roughened by hand using a roughing tool. Tape was applied to the outer edges, and over the center of the clip joint to allow it to continue to flex. Belzona 2911 QD Conditioner was applied and allowed to become touch dry following the instructions for use. Belzona 2111 was then applied, first being scrubbed into the roughened surface, then skim coated over the entire application area and smoothed off by hand to prevent any rough edges or corners.

BELZONA FACTS

Using Belzona 2111 to cover the clip joint prevented countless unscheduled emergency shutdowns and overall reduced the cost of repetitive repairs. This repair paid for itself within one month of normal use at this lumber mill.

INDUSTRY

Not Specified

LOCATION

North Idaho

APPLICATION DATE

August 2016

PRODUCTS

Belzona 2111 (D & A Hi-Build Elastomer)
Belzona 2911 (Elastomer QD Conditioner)

SUBSTRATE

Rubber

PHOTOS

1. Application area cleaned.
2. Roughening the surface by hand prior to applying the Belzona 2911 conditioner.
3. Scrubbing the Belzona 2111 into the application area.
4. Completed application.

For more examples of Belzona Know-How in Action, please visit khia.belzona.com

Belzona products are manufactured
under an ISO 9001 Registered
Quality Management System.

www.belzona.com

