

DISTRESSED WATER PUMP REBUILT AND COATED WITH BELZONA 1341N HYDROPHOBIC COATING

ID: 9731



PROBLEM

Decades of wear and loss of efficiency in pumps. Customer required a Belzona solution.

APPLICATION SITUATION

Pump was taken out of service due to poor performance. Labor and material for the application was \$15,000. Replacement was \$70,000 order and install a new pump.

APPLICATION METHOD

After a grit blast Belzona 1311 was used to rebuild the wear rings and packing areas. Then one coat of Belzona 1321 (Ceramic S-Metal) was applied by brush. This was followed by two coats of Belzona 1341N (Supermetalgilde), a hydrophobic coating for energy efficiency.

BELZONA FACTS

Pump was taken out of service due to poor performance. Labor and material for the Belzona application was \$15,000. Replacement was \$70,000 to order and install a new pump.

INDUSTRY

Power

LOCATION

Chandler, IN

APPLICATION DATE

April 1998

PRODUCTS

Belzona 1311 (Ceramic R-Metal)
Belzona 1321 (Ceramic S-Metal)
Belzona 1341N (Supermetalgilde)

SUBSTRATE

Cast Iron

PHOTOS

1. General damage to the pump casing, wear ring areas, and packing areas.
2. Grit blasted completed and ready for Belzona application.
3. After the wear rings and packing areas were rebuilt with Belzona 1311 (Ceramic R-Metal) the first coat of Belzona 1321 (Ceramic S-Metal) was applied.
4. Two coats of Belzona 1341N (Supermetalgilde) were applied. Pump is ready to be reassembled.

For more examples of Belzona Know-How in Action, please visit khia.belzona.com

Belzona products are manufactured
under an ISO 9001 Registered
Quality Management System.

www.belzona.com

